



### List of Items Furnished With The Toilet Riser Kit:

- A. Toilet Riser
- B. (2) Wax Seals
- C. (2) 1/4" x 6" Long Brass Closet Bolts with nuts and washers
- D. Water Supply Line

### Installation Instructions:

1. Shut off the water supply valve.
2. Flush the toilet.
3. Remove the water supply line connected to the tank and valve.
4. Remove the hex nuts from the base of the toilet.
5. The toilet can now be lifted in an upright position from the floor. \* NOTE: The trap inside the toilet will still contain some water. Two people should be used to lift the toilet to keep from spilling the trap water and to avoid injury.
6. Remove the existing wax ring with a putty knife.
7. Slide the closet bolt into the existing flange.
8. Place one wax ring over the existing flange.
9. Carefully install the toilet riser over the closet bolts.
10. Apply pressure to the top of the Riser to properly seal the wax ring with the existing floor flange.
11. Place the second wax ring on top of the Riser flange.
12. Reinstall the toilet on top of the Toilet Riser.
13. Apply pressure on the bowl to properly seat the toilet.
14. Install the washers and hex nut on the closet bolts (*Do not over tighten*).
15. Install the water supply line furnished with the kit.

Your done.



### Product Care:

The durability of the Riser finish can be best preserved by cleaning only with a soft cloth and soapy water.

**100% Lifetime Guarantee** – We will replace the Riser if it breaks for as long as you own it.